

DAFTAR PUSTAKA

Ang, C.E., dan Loehr, J.E., 2002, "Specimen size effect for fiber-reinforced silty clay in unconfined compression", *Geotechnical Testing Journal*, Vol. 26, No. 2, pp. 191-200.

ASTM International, 2003, *Standard Test Method For Splitting Tensile Strength of Cylindrical Concrete Specimens*, D 5102-96, Pennsylvania, USA.

AP-42, 1995, Lime Manufacturing, in Compilation of Air Pollutant Emission Factors, Vol. I : Stationary Point and Area Sources, Office of Air Quality Planning and Standards, U.S. Environmental Protection Agency, Ch. 11.7.

Bazant, Kazemi, Hasegawa, Mazars, (1991), Size Effect in Brazilian Split-Cylinder Tests: Measurements and Fracture Analysis, *ACI Materials Journal*, 88(3):325-332.

Basha, E.A., Hashim, R., Muntohar, A.S., 2004, "Stabilization of clay and residual soils using cement-rice husk ash mixtures", *Jurnal Teknik Sipil* Vol.5 No. 1 Juni 2004,pp.51-66.

Cai, dkk, 2006, *Effect of Polypropylene Fibre and Lime Admixture on Engineering Properties of Clayey Soil*, *Engineering Geology* 87 :230–240.

Chou, L. (Ed.) (1987) "Lime Stabilization: Reactions, Properties, Design and Construction" TRB State of the Art Report 5, Transportation Research Board, National Research Council, Washington DC.

Consoli, N.C., Montardo, J.P., Prietto, P.D.M., dan Pasa, G.S., 2002, "Engineering behavior of sand reinforced with plastic waste", *Journal of Geotechnical and Geoenvironmental Engineering*, ASCE, Vol. 128, No. 6, pp. 462-472.

Edil, T.B., dan Benson, C.H., 1998, *Geotechnics of industrial by-products*, Dalam: Vipulanandan, C., and Elton, D.J (eds): 'Recycled Materials in Geotechnical Applications', ASCE, Geotechnical Special Publication No. 79, pp.1-18.

Little, D. N., (1995), Stabilization of Pavement Subgrades and Base Courses with Lime, Little, D.N., Evaluation of Structural Properties of Lime Stabilized Soils and Aggregates, Volume 3: Mixture Design and Testing Protocol for Lime Stabilized Soils, National Lime Association.

Little, DN, (1998), Unpublished analysis of deflection data from FWD

Hardiyatmo, C.H., 1992 *Mekanika Tanah I*, PT Gramedia Pustaka Utama, Jakarta.

Hisyam, E.S., 2000, *Pengaruh Serat Karung Plastik Terhadap Parameter Kuat Geser Tanah Lempung*, Tugas Akhir Jurusan Teknik Sipil, Fakultas Teknik UMY, Yogyakarta.

Ikizler, dkk, 2009, *Effect of Fibers on Swelling Characteristics of Bentonite*, 2nd International Conference on New Developments in Soil Mechanics and Geotechnical Engineering, Near East University, Nicosia, North Cyprus.

Ingles, O.G., Metcalf, J.B., 1972, *Soil Stabilization, Principles and Practice*, John Wiley & Son's, Sydney, Australia.

Kaniraj, S.R., dan Havanagi, V.G., *Behavior of Cement-Stabilized Fiber-Reinforced Fly Ash-Soil Mixtures*, Journal of Geotechnical and Geoenviromental Engineering, ASCE, Vol.127, No.7, pp.0574-0584.

Maher, dkk, 1994, Mechanical Properties of Kaolinite/Fiber Soil Composite, Journal of Geotechnical Engineering, Vol. 120(8) : 1381-1393.

Mc. Gown, A., Andrawes, K.Z., Al Hasani, M.M., 1978, "Effect of Inclusion Properties on the Behavior of Sand", Geotechnique, Vol. 28, No.3.

Muntohar, A.S., dan Hashim, R., 2002, *Silica waste utilization in ground improvement: A study of expansive soil treated with LRHA*, Naskah disajikan dalam 4th International Conference on Environmental Geotechnics, 12-14 August 2002, Rio de Janeiro, Brazil.

Muntohar, A.S., 1999, *Pengaruh Kapur dan Abu Sekam Padi pada Perilaku Tanah Lempung*, Makalah Seminar Regional antar PTS Kopertis Wilayah V, 4 September 1999, Universitas Islam Indonesia, Yogyakarta.

Muntohar, A.S., 2000, *Inclusion of randomly rubbish-fibre (RRF) as temporary embankment reinforcement*, Naskah Disajikan dalam Konferensi Nasional Teknik Jalan Ke-6, 6-8 Oktober 2003, Jakarta.

Muntohar, A.S., 2005, *Perilaku Mekanis Perbaikan Tanah Dengan LRHA dan Serat Karung Plastik*, Naskah Jurnal Penelitian.

Muntohar, A.S., 2002, "Utilization of uncontrolled-burnt of rice husk ash in soil improvement", *Jurnal Dimensi Teknik Sipil*, Vol. 4 No. 2, 100-105.

Nataraj, dkk, 1997, *Strength and Deformation Properties of Soils Reinforced With EVA Fibers*, *Geotechnical Investigation*, Vol. 4, pp. 65-70.

- Pakaya , F, 2005, *Perbaikan Sifat Mekanis Tanah Dengan Kapur- Abu Sekam Padi Dan Serat Sampah Karung Plastik*, Tugas Akhir Jurusan Teknik Sipil, Fakultas Teknik UMY, Yogyakarta.
- Rais, M.A., 2004, *Variasi Kadar Air pada Pembuatan Batu-Bata Tanpa Dibakar*, Tugas Akhir Jurusan Teknik Sipil, Fakultas Teknik UMY, Yogyakarta.
- Rahman, M.A., 1986, "Effect of rice husk ash mixtures on geotechnical properties of lateritic soils", *West Indian Journal of Engineering*, Vol. 11 (2), pp. 18-24.
- Rahman, M.A., 1987, "Effect of cement-rice husk ash mixtures on geotechnical properties of lateritic soils", *Journal of Soils and Foundations*, JSSMF, Vol. 27 (2), pp. 61-65.
- Sobhan. K., M. Mashnad., 2003, *Mechanical Stabilization of Cemented Soil-Fly Ash Mixtures with Recycled Plastic Strips*, Journal of Environmental Engineering ASCE, Vol.129, No.10, pp.943-947.
- Soil Stabilization Using Hydrated Lime & Geosynthetic, 2006, PT. Conbloc Infratecno, Intercon Plaza Blok C 20-21, Jl. Meruya Ilir Raya, Jakarta.
- Sihotang, Abinhot, Hazairin, 2002, "Pemanfaatan Kapur dan Pozolan sebagai Bahan Baku Utama Pembuatan Semen Hidraulis Alternatif", Bandung.
- Thompson, M. R., (1966), "Lime Reactivity of Illinois Soils," Journal of the Soil Mechanics and Foundations Division, ASCE, Vol. 92.
- Widianti A., Muntohar A.S., Hartono, E., 2008, Studi Model Embankment Tanah dengan Campuran Kapur-Abu Sekam Padi dan Serat Karung Plastik, Dinamika Teknik Sipil, 8(2):118-126.
- Yoder, E.J., Witczak, M.W., "Properties of pavement components, materials characterization", *Principles of Pavement Design*, second edition.
- Ziegler, dkk, 1998, Effect of Short Polymeric fibers on Crack Developoment in Clays, Japanese Geotechnical Society, Vol. 38 (1) : 247-253.